4 - Side Film Applicator / Bird Applicator

Four Sided film applicators have a flat edges prismatic body making them suitable for applying four sided applications with pre-defined thickness for a flat and relatively strong substrate.

This applicator is suitable for the use of both aqueous acid and alkaline samples. It is made up of high grade non corrosive stainless steel. These applicators are designed to be convenient for handling, easy to use / clean and ideal for the paint and coating industry, cosmetic industry and steel industry.

Standard: **ASTM D 823**

Raj Make

Ref No.	Range (µm)
113/1	30, 60, 90, 120
113/2	25, 50, 75, 100
113/3	50, 100, 150, 200
113/4	5, 10, 15, 20
113/5	100, 200, 300, 400



Coating Width: 90 mm
Total Length : 110 mm

Accessories required for testing:

- Test Charts, Glass Plate
- Glass Beaker
- Spatula
- Impression Pad

Package Includes:

4-Side film applicator and manual.

Ordering Informations:

Ref No. 113/1 Range 30, 60, 90, 120 µm
Ref No. 113/2 Range 25, 50, 75, 100 µm
Ref No. 113/3 Range 50,100, 150, 200 µm
Ref No. 113/4 Range 5,10,15, 20 µm
Ref No. 113/5 Range 100, 200, 300, 400 µm

HSN Code: 90318000