

Standard: IS 101 (Part 4/ Sec.4), ISO 2813, ASTM D523, ASTM D2457, DIN 67530

Features:

Easy to operate Support QC mode to improve measurement efficiency.

Adopting the D65 light source to make sure the accurate measurements.

QC measurement mode for auto qualification.

Providing PC software to generate test reports.

Smooth appearance, and comfortable grip.

Long battery life, energy saving and environmental protection

Technical Specifications:

Measuring Angle

20°, 60°, 85°

Measuring Area

9 x 9 mm, 9 x 15 mm, 5 x 38 mm

Measuring Range

0–2000 GU, 0–1000 GU, 0–160 GU

Minimum Test Material Size

57 mm x 10 mm

Resolution

0.1 GU

Repeatability

± 0.2 GU, ± 0.2 GU, ± 0.2 GU

Measuring Time

1.0 s

Indication Error

0 – 100 GU: ± 1.0 GU; 100 – 2000 GU: ± 1.0% GU

Dimension (L x W x H)

140 x 50 x 75 mm; 300 gms

Battery

Lithium rechargeable 3.7V @ 2000mAh

Interface

USB (Type C)

Software

GlossMeter_PC_V1.8 QC Software to PC through USB

Package Includes:

Gloss Meter, USB Cable, Standard Calibration Plate, Manual, QC software.

Ordering Informations:

Ref No: 227/T

HSN Code: 90275090

